Round bottom flasks

The LABSOLUTE® round bottom flasks made of borosilicate glass 3.3 comply with the valid standards. They are available in different volumes and have the common ground joint sizes. All LABSOLUTE® round bottom flasks are characterized by very good chemical and temperature resistance. Because of the round shape, the flasks are ideal for consistent heating of liquids. Due to the standard ground joints, the flasks can be easily combined with other glass labware such as condensers.

1

1 Round bottom flasks, with standard ground joint, borosilicate glass 3.3

NEW

Comply with DIN EN ISO 4797.

Capacity ml	Socket NS	Flask Ø mm	Height mm	PK	Cat. No.
10	14/23	33	70	1	**7.690 100**
25	14/23	41	85	1	**7.690 101**
50	14/23	51	90	1	**7.690 102**
50	29/32	51	90	1	**7.690 103**
100	14/23	64	105	1	**7.690 104**
100	29/32	64	105	1	**7.690 105**
250	29/32	85	140	1	**7.690 106**
500	29/32	105	163	1	**7.690 107**
1000	29/32	131	200	1	**7.690 108**
2000	29/32	165	240	1	**7.690 109**

2

9.011 850

Round bottom flasks with conical ground joint, DURAN®

According to DIN EN ISO 4797 and in addition to DIN standard (*), with inscription label, material: DURAN®.

Lenz

Capacity ml	Flask diam. mm	Socket NS	PK	Cat. No.
5	30	14/23*	1	**6.201 199**
10	35	14/23*	1	**9.011 801**
25	41	14/23	1	**9.011 802**
25	41	19/26	1	**7.021 797**
50	51	14/23	1	**9.011 805**
50	51	19/26	1	**6.302 116**
50	51	24/29	1	**7.019 181**
50	51	29/32	1	**9.011 835**
100	64	14/23	1	**9.011 810**
100	64	19/26	1	**6.200 675**
100	64	24/29	1	**7.019 182**
100	64	29/32	1	**9.011 840**
250	85	14/23*	1	**9.011 815**
250	85	19/26*	1	**6.800 202**
250	85	24/29	1	**6.800 214**
250	85	29/32	1	**9.011 845**
250	85	45/40*	1	**9.011 867**
500	105	24/29	1	**6.800 215**
500	105	29/32	1	**9.011 850** 2
500	105	45/40	1	**9.011 868**
1000	131	24/29	1	**6.800 235**
1000	131	29/32	1	**9.011 855**
1000	131	45/40	1	**9.011 869**
2000	166	29/32	1	**9.011 860**
2000	166	45/40	1	**9.011 870**
3000	185	29/32*	1	**6.077 738**
3000	185	45/40*	1	**6.901 617**
4000	207	29/32	1	**9.011 865**
4000	207	45/40	1	**9.011 875**
5000	223	29/32*	1	**9.011 864**
5000	223	45/40	1	**9.011 877**
6000	236	29/32*	1	**9.011 866**
6000	236	45/40	1	**9.011 880**
10000	279	45/40	1	**9.011 885**

E & OE.